

Color Micro Dome Camera

New High Resolution Day/Night Version!

in focus...

- ▶ 480 Lines of Resolution (CDC3019HR/DN)
- ▶ 420 Lines of Resolution (CDC3019)
- ▶ Low 0.1 Lux @ F2.0 Rating (CDC3019HR/DN)
- ▶ Low 0.3 Lux @ F2.0 Rating (CDC3019)
- ▶ Built-in AWB, AGC, & Electronic Shutter
- ▶ 3.6mm 72° Field of View Lens
- ▶ Efficient 12-Volt @ 100mA Operation
- ▶ Small 2.8" Diameter x 2.1" High

Who said great things don't come in small packages? All of the CDC3019 micro dome cameras pack a host of features in a truly tiny and stylish 2.8" dome housing. They are so small that they will blend into almost any office or home environment with ease. The superhigh-resolution CDC3019HR and CDC3019DN produces over 480 lines of resolution giving you detail you might only expect from much larger dome cameras costing twice as much. The CDC3019 offers a great 420 lines of resolution at an unheard-of price of only \$69. All three units come with EZ-connect cables.



[CDC3019 SERIES]

specifications | CDC3019 Series

Image Sensor	1/3" Color CCD
Resolution	480 TVL HR/DN Version & 420 CDC3019
Pixel	(HxV) NTSC: 768 x 494, PAL: 752 x 582
S/N Ratio	More than 48 dB
Electronic Shutter	NTSC: 1/60s ~ 1/100,000s, PAL: 1/50s ~ 1/100,000s Auto Switchable
Gamma	0.45
White Balance	Automatic (2500°K ~ 9500°K)
Sync Control	Internal
Lens	3.6mm F2.0
Video Output	Composite Video 1.0Vp-p at 75Ω
Power Supply	12VDC ± 10% / 1.8W / 100mA
Operating Temp.	-10 °C to 50 °C (14 °F to 122 °F)
Dimension	2.8" D x 2.1" H

WWW.SCDLINK.COM

1 SECURITY CAMERAS DIRECT WAY
LULING, TX 78648
PHONE: 800.316.6027
830.401.7000
FAX: 830.875.9010

SECURITY CAMERAS
DIRECT