

5-50mm Varifocal Vandal Dome

Super Sharp 540 Lines of Resolution

in focus...

- ▶ 540 Lines of Resolution DSP Color
- ▶ 0.002 Low Light Lux @ F1.2
- ▶ Varifocal 5-50mm Zoom Auto Iris Lens
- ▶ On Screen Display & Digital Noise Reduction
- ▶ Privacy Masking Zone & Motion Detection
- ▶ Size 6.8"D x 5.2"H
- ▶ Versatile Dual Voltage 12VDC & 24VAC

Our new CDC3031VF will ensure you have a sharp eye on the view you need even at large distances. The Sony HQ-1 chipset produces a vibrant 540 lines of resolution and a low 0.002 lux rating for great image clarity in all low light situations. With the user selectable BLC, AGC and DNR you will have the power to dial in a perfect picture fast and easy. The built-in day night feature even allows you to decide what light level to switch to low light B/W. With the 4 zone motion detection you can trigger your security VCR or DVR to record only the action you want, without using up valuable HDD or tape space. The 4 zone privacy masking makes this camera great for sensitive viewing areas like dressing, bath and locker rooms. All of the above functions can be easily adjusted with the innovative on screen display. With the rugged weatherproof and vandal proof housing this camera is great for use in parking lots, traffic observation or high security areas.



[CDC3031VF]

specifications | CDC3031VF

Power Source	DC 12V & AC 24v (Dual Voltage)
Power Consumption	280mA(DC) / 3.8W(AC)
Image Sensor	1/3", SONY SUPER HAD CCD, 410,000 pixels
Total Pixels	811(H) x 508(V), 1/3" CCD
Effective Pixels	768(H) x 494(V), 1/3" CCD
LENS Type	DC AUTO IRIS VARIFOCAL 5~50mm
Maximum Aperture Ratio	1 : 1.3 ~ 2.0
Scanning System	2 : 1 Interlaced 525 Lines / 60 Fields / 30 Frames
Synchronization	Internal / Line Lock selectable
Video Output	1.0V [p-p] NTSC Composite, 75Ω / BNC Connector
Resolution	540 TV Line
Gain Control	AGC-L, AGC-H, OFF selectable
Electric Shutter Speed	1/60 ~ 1/200,000 sec
INTENSIFIER	Built-in (selectable limit ~ X128)
WHITE BALANCE	ATW / AWC / MANUAL
Min. Illumination	0.002Lux (intensifier) 0.3Lux(sh)
S/N (Y signal)	50dB (Weight On)
DNR	OFF / LOW / MIDDLE / HIGH
Motion Detection	ON / OFF
On Screen Display (O.S.D)	Built - in
PRIVACY Function	ON / OFF (4 Programmable Zone)
Operational Temperature	-10°C ~ +50°C (14°C ~ 122°C)
Operational Humidity	30% ~ 90% RH(save on pc or print picture by picture in jpeg format or in AVI format)

WWW.SCDLINK.COM

1887 S. STATE HWY 80
LULING, TX 78648
PHONE: 800.316.6027
830.401.7000
FAX: 830.875.9010

SECURITY CAMERAS
DIRECT