

# Mini 3-Axis High Resolution Vandal Dome Camera

*Extreme Durability In A Tiny Form Factor*

## in focus...

- ▶ 480 LOR Sony Super HAD
- ▶ 0.1 Low Light Lux Rating
- ▶ Rugged All Metal Housing
- ▶ 3.6mm 80° FOV Mini Lens
- ▶ Power 12VDC @ 160mA
- ▶ 2.7" Diameter x 2.1" Depth



This camera is small in size but is built rugged for harsh environments and locations. This camera has a unique swivel turret design that rotates on 3-axis. This makes installation faster and easier. It uses the Sony Super HAD chipset that uses digital signal processing for razor sharp images. At only 2.7 inches in diameter these cameras will blend into your environment with ease. It is perfect for professional office and retail store installations. The IP66 rating means you can even mount this camera outdoors for a complete range protection.

[CDC3038ST]

## specifications | CDC3038ST

Image Sensor	1/3" Sony Super HAD CCD Sensor
Effective Pixels	NTSC=768(H) * 494(V) PAL=752(H) * 582(V)
Scanning System	2:1 Interlaced
Sync System	Internal Sync
Resolution	480 TV Lines
Usable Illumination	0.1 Lux
S/N Ratio	More than 45dB
Video Output	Composite Video Signal : 1.0Vp-p 75 ohm
Electronic Shutter Time	NTSC=1/60 ~ 1/100,000 Sec PAL=1/50 ~ 1/100,000 Sec
Power Supply	DC 12V
Power Consumption	160mA
Lens	3.6mm
Operating Temperature	-10°C ~ +50 °C RH95% Max
Storage Temperature	-21 °C ~ +60 °C RH95% Max
Dimension	2.72" (W) x 2.17" (D)

[WWW.SCDLINK.COM](http://WWW.SCDLINK.COM)

1887 S. STATE HWY 80  
LULING, TX 78648  
PHONE: 800.316.6027  
830.401.7000  
FAX: 830.875.9010

**SECURITY CAMERAS**  
**DIRECT**