

Wide Dynamic Dome Cameras

Perfect For Convenience Stores

in focus...

- ▶ 530 LOR Sony Super HAD 1/3" CCD
- ▶ Low 0.002 Low Light Lux Rating @ F1.6
- ▶ Up to 30 FPS 740 X 480 Resolution
- ▶ Vari-Focal DC Auto Iris 5-50mm Lens
- ▶ 20 Concurrent Users with Password Protection
- ▶ Built-in Video Motion Detection
- ▶ Alarm Feature can E-mail/SMS Images
- ▶ 12-Volt DC @ 545mA

These super high resolution weatherproof cameras will allow you to keep an eye on your office or home anywhere in the world via internet. The integrated video motion detector can trigger the cameras to record images only when action is detected and save valuable hard-drive space. The MPEG4 compression can give you up to 30 images per second for true live images. Other advanced features include security watermark, event triggered e-mail, Ethernet (10/100 base), 530 lines of resolution, heavy-duty aluminium housing and bracket. Requires Windows 2000/XP with 256MB of memory.



[CDC3040IP]

specifications | CDC3040IP

Image Sensor	1/3" Sony Super HAD CCD, 410,000 pixels	
Total Pixel	NTSC	811(H)*508(V)
Effective Pixel	NTSC	768(H)*494(V)
Horizontal resolution	530 TV Lines	
Minimum Illumination	0.002 Lux(Sense-up 128x)	
S/N Ratio	50dB(Weight On)	
Lens	Vari-Focal, f=5~50mm	
Maximum Aperture Ratio	1:1.7	
Angle of View	H:74.2' ~ 30.0', V:54.0' ~ 22.4', D:96.8' ~ 37.4'	
Scanning System	2:1 Interlaced 525 Lines/60 Fields/30Frames	
Synchronization	Internal	
Compression	MPEG4/JPEG	
Multi-Streaming	MPEG4(2ch), JPEG(1ch)	
Gain Control	Low / Middle / High / Off	
Electric Shutter Speed	1/60 ~ 1/200,000sec	
Sense Up	Built-in(selectable Limit ~ X128)	
White Balane	ATW / AWC / Manual	
Digital Noise Reduction(DNR)	Low / Middle / High / Off	
Audio	Bi-Directional	Yes(Optional)
	Compression	G.723(Optional)
Video Output	1.0 Vp-p 75 ohm Composite	
Dimension	133.5mm(H) * 178mm(D)	
Power Source	DC 12V	
Power Consumption (Max.)	6W	
Operational Temperature	-10 deg - +50 deg C RH95% MAX(14 deg F to 122 deg F)	
Weight	1.4kg	

WWW.SCDLINK.COM

1887 S. STATE HWY 80
LULING, TX 78648
PHONE: 800.316.6027
830.401.7000
FAX: 830.875.9010

SECURITY CAMERAS
DIRECT