

Color Vandal Domes

Dual Voltage 12VDC/24VAC

in focus...

- ▶ Weatherproof IP-66
- ▶ 3-Axis Camera Mount
- ▶ Auto Sensing Power
- ▶ Optional D/N Versions



Our latest generation vandal dome cameras will amaze you with their picture quality. With your choice of a 4-9 or 2.6-6mm aspherical lens you will be able to get the perfect shot every time. With the ability to use either installer friendly 24VAC or 12VDC, powering these cameras is both fast and easy. The durable and weatherproof enclosure ensures that these cameras withstand up to even the harshest conditions. The internal 3-Axis camera bracket allows you to even mount these cameras directly on a wall and still achieve a perfect picture.

[CDC3053/54 SERIES]

specifications | CDC3053/54 Series

Model #	CDC3053VF	CDC3054VF	CDC3053EX	CDC3054EX	CDC3053VF2	CDC3054VF2
Power Source	Dual Voltage 12VDC & 24VAC					
Chipset	1/3" Sony Super HAD CCD		1/3" Ex-View Inter Line CCD		1/3" Sony Super HAD CCD HQ1	
Scanning System	2:1 Interlace					
Video Output	1.0V (p-p) NTSC Composite					
Min Illumination	0.5 LUX at F1.2					
Resolution	450 TV Lines		550 TV Lines		600 TV Lines	
BLC	Built In (On)					
Electronic Shutter	1/30 ~ 1/100,000 sec					
White Balance	AWB					
Lens	4-9mm	2.6-6mm	4-9mm	2.6-6mm	4-9mm	2.6-6mm
AGC	Built In (On)					
S/N Ratio	More than 48dB (AGC Off)					

WWW.SCDLINK.COM

1 SECURITY CAMERAS DIRECT WAY
LULING, TX 78648
PHONE: 800.316.6027
830.401.7000
FAX: 830.875.9010

SECURITY CAMERAS
DIRECT