

# 550 Lines Easy Install Mini Dome Camera

*With Convenient External Tilt Adjustment!*

- ◆ 550 Lines of Resolution
- ◆ 3.6mm Fixed lens
- ◆ External Pan/Tilt Adjustment
- ◆ 12VDC @ 250mA
- ◆ Low 0.1 Lux @ F2.0 Rating
- ◆ Built-in AWB, AGC, & Electronic Shutter
- ◆ Quick and Easy Install



550

LOR

0.1

Lux

12VDC

Voltage

Day/Night

CDC3062ST

## specifications | CDC3062ST

Signal system	NTSC    PAL
Image Sensor	Lumii Sensor
Effective pixels(HxV)	720 x 480    720 x 576
Electronic	
Scanning System	"2:1 Interlace
V: 59.94Hz,H: 15.734KHz"	"2:1 Interlace
V: 50Hz,H: 15.625KHz"	
Sync system	Internal
Horizontal resolution	550 TVLines
Lens	f=3.6mm, F2.0
Auto White Balance	Auto (2500°K to 9500°K)
Electronic Shutter	Auto
Aperture	Auto
AGC	Auto
BLC	Auto
Minimum illumination	0.4lux/ F2.0/ 50IRE
S/N Ratio	> 52dB
Power supply	
Power requirement	DC12V ± 10%
Power Consumption	0.65 W
Environment	
Operating temperature	-10°C ~ 50°C (14 °F ~ 122 °F)
Operating humidity	90% RH
Storage temperature	-20°C ~ 60°C (-4 °F ~ 140 °F)
Mechanism	
Easy adjustment	External 350 ° pan direction rotation, 75 ° tilt direction adjustment
Dimensions (D X H)	107mm x 64 mm
Ordering information	550DIFW-HN1    550DIFW-HP1

[WWW.SCDLINK.COM](http://WWW.SCDLINK.COM)

1 SECURITY CAMERAS DIRECT WAY  
LULING, TX 78648  
PHONE: 800.316.6027  
830.401.7000  
FAX: 830.875.9010

