

4 Channel H.264 Networkable DVR

Increase Recording Time Without Reducing Video Quality



- ◆ H.264 Real-Time Recording
- ◆ 352 x 240 120FPS to 704 x 480 30FPS
- ◆ Video Motion Detection w/ 16 x 12 Grid
- ◆ Alarm Inputs & Output
- ◆ VGA & BNC Monitor Outputs
- ◆ Quick Search Date/Time, Alarm & List
- ◆ Auto E-mail of Alarm Events
- ◆ 2X Digital Zoom Live & Playback
- ◆ USB 2.0 or Network Offload
- ◆ RS-485 PELCO-D/P Protocol



[DVR4060N]

specifications | DVR4060N

Video Format	H.264
Video Input	4 Channel BNC
Audio Input/Output	1 Audio Input & 1 Audio Output
Recording Resolution	352 x 240 120FPS to 704 x 480 30FPS
Built-In OSD	Multi-Lingual OSD
Image Quality Setting	Super, Best, High & Normal
Hard Drive	SATA Hard Drive (1TB MAX)
Search Function	Time & Motion Search Mode
VGA Interface	Built-in VGA (Max Output Resolution 1600 x 1200)
Recording Mode	Manual, Timer, Motion & Remote
Pre-alarm Recording	Built-in (8MB)
Backup Device	USB 2.0 Flash Drive or Network Offload
Web Compression	H.264
Network Protocol	TCP/IP, PPPOE, DHCP & DDNS
Web Interface1	Internet Explorer or Mozilla Firefox (Video Viewer Software)
Web Interface2	20 Users Simultaneously
Web Interface3	Works with Windows Vista, XP, 2000; Apple MAC
Remote Control	IR Remote Control Included
Power	19VDC @ 42 Watts
System Recovery	Auto Recovery After Power Failure

WWW.SCDLINK.COM

1 SECURITY CAMERAS DIRECT WAY
LULING, TX 78648
PHONE: 800.316.6027
830.401.7000
FAX: 830.875.9010

SECURITY CAMERAS
DIRECT