



Micro Pocket DVR

Record Up to 400 Minutes of Audio/Video

in focus...

- ▶ 30 FPS 352 x 240 LOR Recording
- ▶ MPEG-4 Video Recording
- ▶ Supports 1 Channel of Audio
- ▶ Time & Date Stamp
- ▶ Runs On 2 AA Batteries (Not Included)
- ▶ Small 2.5" W x 3.5" H x 1.1" D

Our new MPE1009 makes it easy to capture audio/video from any of our cameras. With this DVR you can set up your recording schedule to meet your needs. You can set it up to record on motion, time, or manual recording. The playback log is simple to use. It let's you know while playing back video what kind of recording occurred whether it was a motion, manual, or time recording. This DVR also allows you to connect to your PC via USB cord to off load your video or you can put your SD card into a card reader and view the video in Windows Media. The MPE1009 let's you rest assured that the recording occurred with the state of the art time & date stamp. This DVR is perfect for those covert or mobile recordings with it's compact size and weight. SD card is not included.



[MPE1009]

specifications | MPE1009

| | |
|--------------------------|---|
| Video System | NTSC / PAL with Video Loss Auto Detection |
| Video Codec | MPEG4-SP ASF File Format |
| Video Record Frame Rate | (NTSC / PAL) Max. 704x480@24 fps / 704x576@19 fps |
| Video Record Quality | High / Medium / Low |
| Video Recording | Date / Time Overlay with Video Images in ASF File |
| Video Input | 1 CH, Phone Jack |
| Video Output | 1 CH, Phone Jack |
| Audio Sampling Rate | 44.1 KHz |
| Audio Codec | G.726 / 32 kbps |
| Audio Input | 1 CH, Phone Jack |
| Audio Output | 1 CH, Phone Jack |
| Storage Media | Secure Digital (SD) Card |
| Recording Mode | Schedule / Motion Detection / Manual |
| Motion Detection Setting | Multiple Blocks and adjustable sensitivity |
| Playback Function | Play / Fast Forward / Fast Rewind / Pause / Step Forward / Step Rewind |
| Playback Speed | x1 / x2 / x4 / x8 / x16 / x32 |
| Power Supply | AC100~240V 50/60 Hz, DC5V / AAx2 Batteries Rechargeable Ni-MH / Alkaline Battery / CR-V3 / RCR-V3 Power Consumption 2.5W max. |
| Weight | 150 g (without Battery) |
| Dimensions (WxHxD) | 90x65x27 mm |
| Operating Environment | 30~80% RH, 5° C ~ 45° C (41° F ~ 133° F) |

WWW.SCDLINK.COM

1887 S. STATE HWY 80
LULING, TX 78648
PHONE: 800.316.6027
830.401.7000
FAX: 830.875.9010

SECURITY CAMERAS
DIRECT