

Diversity Receivers

Increase Your Range and Clarity

[REC2400DV]

in focus...

- ▶ 2.28-2.49GHz w/5 Channels
- ▶ 4 Omnidirectional 3dB Antennas
- ▶ Video Bandwidth 30 Hz - 5MHz
- ▶ Power 7-30VDC @ 160mA
- ▶ Receiver Size 4.1" W x 1.9" H x 3.9" D

This diversity receiver will dramatically improve your video reception and decrease the disturbance of video and audio caused by reflections of microwave that occur when signals pass through walls and other obstacles. This smart receiver evaluates the best frequency and switches to the most suitable signal, this happens 20 times a second. This receiver is well suited for vehicular and mobile application that are particularly difficult to lock in a stable signal. Call today and have a clear signal tomorrow.



specifications | REC2400DV

Video Output	Composite color picture signal, pos. 1 ± 0,1VPP an 750hm, adjustable 0.5 - 1.5VPP
Video bandwidth	30Hz - 5MHz
Audio output A + B	500 mVeff an < 1kOhm
Audio bandwidth	15 Hz - 15 kHz
Tuner sensitivity	
Sensitivity gain limited on the tuner input	-94dBm ^ 13dBμV
Sensitivity noise limited on the tuner input	-86dBm ^ 21dBμV bei SN 12dB
Modulation mode	F3F (Video/ Audio)
Switching channel frequency	optional Ton A 32kHz
Switching channel output	15V / 80mA open collector
Power supply DC	7 - 30V DC
Current consumption	160mA bei 12V
Antenna	4 omnidirectional antennas
Dimensions	Receiver: 4.1" W x 1.9" H x 3.9" D Diversity-Box: 2.68" x 1.5" x 3.27"
Weight	Receiver: 450g / Diversity-Box: 200g

WWW.SCDLINK.COM

1887 S. STATE HWY 80
LULING, TX 78648
PHONE: 800.316.6027
830.401.7000
FAX: 830.875.9010

SECURITY CAMERAS
DIRECT